

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**(19) World Intellectual Property
Organization
International Bureau**



(43) International Publication Date
29 April 2004 (29.04.2004)

PCT

(10) International Publication Number
WO 2004/036564 A1

(51) International Patent Classification⁷: G11B 7/125
(21) International Application Number: PCT/JP2003/012800

(22) International Filing Date: 6 October 2003 (06.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2002-302934 17 October 2002 (17.10.2002) JP

(71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571-8501 (JP).

(72) Inventors; and

(75) **Inventors/Applicants (for US only):** ISHIBASHI, Hiromichi [JP/JP]; 2-6-H-503, Tenno, Ibaraki-shi, Osaka 567-0876 (JP). SHIHARA, Tetsuya [JP/JP]; 3-26, Doyamacho, Kadoma-shi, Osaka 571-0059 (JP). SENG, Hisashi [JP/JP]; 3-14-527, Miyukihigashimachi, Neyagawa-shi, Osaka 572-0055 (JP). MATSUMOTO, Toshio [JP/JP]; 7-2-1-301, Katsura Chiyoharacho, Nishikyo-ku, Kyoto-shi, Kyoto 615-8085 (JP).

(74) Agent: **OKUDA, Seiji**; OKUDA & ASSOCIATES, 2nd Floor, Kataoka Bldg., 3-6, Uchiawajimachi 1-chome, Chuo-ku, Osaka-shi, Osaka 540-0038 (JP).

(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: OPTICAL DISC DRIVE



(57) Abstract: In an optical disc drive, a laser light source emits a laser beam having an intensity changeable with the amount of drive current supplied. A first photodetector receives the laser beam reflected from an optical disc, thereby generating a readout signal. A second photodetector receives the laser beam, generates an electric signal representing the power of the laser beam received, and outputs the electric signal as a light quantity detection signal. A feedback control loop compares the level of the light quantity detection signal with a predetermined target value and regulates the drive current such that the level of the light quantity detection signal approaches the target value. In reading data from the optical disc, the target value is changed so as to compensate for a variation of the sensitivity of the second photodetector, thereby controlling the power of the laser beam emitted from the laser light source.

WO 2004/036564 A1